

Z700 Series

Specifications

Z723 - Z724 - Z725 - Z724X - Z726X



Model		Z700						
		Z724XKW-48	Z724XKW-54	Z726XKW-60	Z723KH-48	Z724KH-54	Z725KH-60	
Engine	Model	GH735V						
	Type	Gasoline, air-cooled V-Twin						
	Max. horsepower (Gross)	HP	23.5*	25.5*	22.5**	23.5**	25**	
	Total displacement	cu. in. (cc)	44 (726)	52 (852)	42 (694)		46 (747)	
	Starting system	Key switch						
Dimensions	Overall length	in. (mm)	83.9 (2130)					
	Overall width	(w/ mower) in. (mm)	61.3 (1557)	67.3 (1710)	73.8 (1875)	61.3 (1557)	67.3 (1710)	73.8 (1875)
		(w/o mower) in. (mm)	50.4 (1280)		54.7 (1390)	50.4 (1280)		54.7 (1390)
	Overall height	(w/ ROPS upright) in. (mm)	69.9 (1775)					
		(w/ ROPS folded) in. (mm)	48.3 (1226)					
Wheel base		in. (mm)	50.9 (1294)					
Tread	Front	in. (mm)	37.6 (954)					
	Rear	in. (mm)	40.2 (1020)		42.6 (1083)	40.2 (1020)		42.6 (1083)
Tire size	Front		13 x 5.0 - 6 Non flat		13 x 6.5 - 6 Non flat	13 x 5.0 - 6 Non flat		13 x 6.5 - 6 Non flat
	Rear		24 x 9.5 - 12		24 x 12 - 12	24 x 9.5 - 12		24 x 12 - 12
Weight (w/ mower)		lbs. (kg)	1163.0 (527)	1179.0 (535)	1232.0 (559)	1168.4 (530)	1181.7 (536)	1212.5 (550)
Transmission			Parker Torqpack GT14					
Transmission system			1 HST - G rotor type					
Speed control			2-hand lever					
Travel speed range	Forward	mph (km/h)	0-11.2 (0-18)					
	Reverse	mph (km/h)	0-5.6 (0-9)					
Brake type			Drum disks, foot applied, released					
PTO	Type		Belt drive					
	Clutch type		Electric clutch					
	PTO brake		Dry disc					
Mower deck	Model		RCK48P-723Z	RCK54P-724Z	RCK60P-725Z	RCK48P-723Z	RCK54P-724Z	RCK60P-725Z
	Mower lift system		Mechanical					
	Mower deck type		Commercial fabricated deck					
	Deck depth	in. (mm)	6.0 (152)					
	Belt type		Single belt					
	Deck steel thickness	Ga (mm)	8 (4.18)					
	Anti-scalp roller		Rigid					
	Cutting width of mower	in.	48 (1219.2)	54 (1371.6)	60 (1524)	48 (1219.2)	54 (1371.6)	60 (1524)
	Number of blades		3					
	Cutting height		1.0 in. - 5.0 in. 1/4 in. increments					
	Mower mounting system		Parallel linkage					
	Blade tip speed (max.)	FPM	18100			18600		
Engine stop system			Key stop					
Fuel tank capacity		gals. (ltrs.)	11.6 (43.9)					
Battery			U1 (12V, RC: 45min, CCA: 300, CA: 410)					
Generator capacity		Amp	15A					
Hour meter			Standard					
Fuel gauge			Electric gauge type					

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

**Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a roll over protective structure (ROPS) and seatbelt in almost all applications.